

# LEDDriving BASIC P21W



## Product family datasheet

### Technical data

Product description	Product information		General Product Information	Electrical Data	
	Product type (off-road vs. on-road)	Application (Category and Product specific)	Global order reference	Power input	Nominal voltage
LEDriving BASIC $\cong$ P21W	Off-road $\cong$ P21W	Mainly used for signal/ indicator applications	7356CW	1.44 W	12.0 V

Product description	Nominal wattage	Test voltage	Photometric Data		Physical Attributes & Dimensions
			Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC $\cong$ P21W	1 W	13.5 V	85 lm	$\pm$ 20 %	20.0 mm



Product description	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
	Lifespan B3	Lifespan Tc	Technology	Primary article identifier	Candidate list substance 1
LEDriving BASIC $\cong$ P21W	2000 hr	2000 hr	LED	4052899463318   4052899414471   4052899414457	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC $\cong$ P21W	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	d093b426-00c5-4f97-9516-27dd98167ef2   ccdfe44b-95fd-4b60-97d3-317a31be77c4   c583693a-46e5-4c4f-83a9-dac2ada6ba15

## Product family datasheet

---

### Download Data

File	
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

#### Legal advice

Not ECE conform Only approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

#### References / Links

Guarantee terms are available at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

