OSRAM

LEDriving BASIC P21/5W



Product family datasheet

2000 hr

2000 hr

LED

4052899463295 |

4052899414518 | 4052899414495 Lead

Technical data

	Product information		General Product Information	Electrical Data		
Product description	Product type (off- road vs. on-road)		tion (Category oduct specific)	Global order reference	Power input	Nominal voltage
LEDriving BASIC ≜ P21/5W	Off-road ≜ Mainly used for P21/5W signal/ indicator applications		1357CW	1.44 W	1.44 W 12.0 V	
				Photometric Data		Physical Attributes & Dimensions
Product description	Nominal wat	tage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Diameter
LEDriving BASIC	1 W		13.5 V	85/25 lm	±20 %	20.0 mm
	Lifetime Data		Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Lifespan L B3 T	ifespan c	Technology	Primary article identifier	Candidate substance	

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
LEDriving BASIC	7439-92-1	The identification of	9bf3b981-7442-
		the Candidate List	439c-a86d-
		substance is	e513fc794734
		sufficient to allow	fe6d71fd-c80e-400d-
		safe use of the	8cc2-14ed29394294
		article.	1d480114-7d33-
			4144-80cc-
			0d5f7210d25e

Product family datasheet

Download Data

File



User instruction

GPRS_Safety symbols instructions



Brochures

LEDriving Retrofits - Exchange overview (EN)

Legal advice

Not ECE conformOnly approved for off-road use. Any use on public road traffic leads to cancellation of vehicle operating licence and loss of insurance cover.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

