Product family datasheet

OSRAM

Round MX260-CB



ECE certified - ECE R7R112

The necessary tests and approvals were carried out and an ECE type approval was granted2)ECE reference number: 50



Combo Beam

Designed for both: far-field and near-field illumination. For widespread illumination in the near field and spot illumination in the far field.



Light beam up to 350 m length See and be seen with OSRAM

See and be seen with oslovin



On-road & Off-road

Versatile applicable and flexible in use.On-road & offroad, in terrain, at work and in the spare time.



Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Round MX260-CB. With its 16 powerful, high-performance long-life LEDs, the OSRAM LEDriving Round MX260-CB has a range of up to 350 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Round MX260-CB with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 3500 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road.Whether on-road or off-road - The OSRAM LEDriving Round MX260-CB impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Round MX260-CB has been tested and validated with the IP-Protection Class IP69K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED driving light and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Round MX260-CB is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECEcertified LED driving lights2).ECE reference number: 50The OSRAM LEDriving Round MX260-CB can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and guads2). The OSRAM LEDriving Round MX260-CB is versatile applicable and flexible in use.2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

Product family datasheet

Technical data

	Product inf	Product information Application (Category and Product specific)		General Product Information			Electrical Data			
Product description				Global order reference		iinal voltage	9	Nominal wattage		
Round MX260-CB ¹⁾		Additional high beam and position light		LEDDL112-CB		12/24 V		60 W		
		Photomet	netric Data LED modu informatio				Capabilities			
Product description	Test voltage	Nominal l flux	uminous Number of LEDs per module		f	Lifespan Tech Tc		nology		
Round MX260-CB 1)	13.5 V	3500 lm		10/36		5000 hr	LED	2)		
	Certificates	s & standard	s							
Product description	Approval m approval	••		Type of protection		ards		ECE reference number		
Round MX260-CB 1)	E4 approva	ıl	ІР69К		ECE R	10, R112, R	7	50		
	Logistical data Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 190 (REACh)					(EC) 1907/2006				
Product description	Commodity	Commodity code		Candidate list substance 1		CAS No. of substa 1		Safe use instruction		
Round MX260-CB ¹⁾	851220009	900	Lead		7439	9-92-1		The identification of the Candidate List substance is sufficient to allow safe use of the article.		

Product description	Declaration no. in	
	SCIP database	
Round MX260-CB 1)	246a6055-9187-	
	4234-b752-	
	7854dd85d91f	

¹⁾ Beam Pattern: Combo

 $^{2)}$ Light-emitting diode application

Product family datasheet

Download Data

	File
7	User instruction LEDriving Round MX260-CB
*	User instruction GPRS_Safety symbols instructions
D	Movie application LEDriving D and W Image Video Bringing light to life (EN)
D	Movie application Working and Driving Lights Amarok Winter
D	Movie application LEDriving Driving and Working Lights Reference Video (EN)
D	Movie application OSRAM LEDdriving and working lights Imagefilm (EN)
D	Movie application OSRAM Quality Testing LEDriving working and driving lights (EN)
D	Video Light is Quality -OSRAM LEDriving Driving and Working Lights Quality Tests (EN)
D	Video OSRAM LEDriving driving and working lights: The night doesn't stand a chance
D	Video OSRAM LEDriving driving and working lights in action - From on road to off road applications (EN)
D	Video Reference Number made easy - Making sure your LEDriving Driving Lights are legal on public roads

Legal advice

Legal advice:

The installation of the OSRAM LEDriving Round MX260-CB is fully ECE compliant and therefore registration free. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product.

1) Precise terms and conditions at: www.osram.com/am-guarantee

2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.Refer to www.osram.com/am-guarantee for precise conditions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.