## Product family datasheet

# **OSRAM**

# Lightbar VX1000-CB SM



### Double ECE-Certification - 2 x ECE R112

The necessary tests and approvals were carried out and an ECE type approval was granted2)Central single mount possibleECE reference number: 37.5 + 37.5



Combo Beam

Designed for both: far-field and near-field illumination. For widespread illumination in the near field and spot illumination in the far field.



Up to 525m long light beam

See and be seen with OSRAM.Special curved reflector design with extraordinary perforation.



**On-road & Off-road** 

Versatile applicable and flexible in use.On-road & offroad, in terrain, at work and in the spare time.



# Bringing light to life with OSRAM LEDriving driving and working lights

Considerable foresight on dark country roads, forest paths, off the beaten tracks, off-road and on-road- this can be achieved with the OSRAM LEDriving Lightbar VX1000-CB SM. With its 36 powerful, high-performance OSRAM long-life LEDs, the VX1000-CB SM has a range of up to 525 meters and thus offers the driver impressive foresight on-road and off-road. Even in dim light and reduced visibility due to external environmental influences, the OSRAM LEDriving Lightbar VX1000-CB SM with up to 6000 Kelvin can provide conditions similar to daylight. The power package with up to 6000 lumens of luminosity scores with highest optical efficiency and homogeneous light distribution. This results in the possibility of an improved view for you and the improved visibility of your vehicle by other road users, and consequently also increased safety on-road and off-road.Whether on-road or off-road - The OSRAM LEDriving Lightbar VX1000-CB SM impresses with its powerful performance and a long service life with up to 5000 hours. Versatile applicable, it defies numerous environmental influences and, thanks to highquality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. The OSRAM LEDriving Lightbar VX1000-CB SM has been tested and validated with the IP-Protection Class IP67 in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. The integrated driver and the thermal management system regulate the temperature of the LED Lightbar and can thus prevent damage from overheating. The polarity protection inhibits the wrong polarity of the voltage supply and can thus prevent possible damage by automatically switching off the LEDs. On-road and off-road, the OSRAM LEDriving Lightbar VX1000-CB SM is an effective and efficient addition to your vehicle. No registration or entry in the vehicle documents is necessary for these ECE-certified LED driving lights 2)ECE reference number: 37.5 + 37.5The OSRAM LEDriving Lightbar VX1000-CB SM can be attached to cars, trucks, agricultural machinery, farm machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and guads 2)The OSRAM LEDriving Lightbar VX1000-CB SM is versatile applicable and flexible in use.2) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.

# Product family datasheet

### Technical data

|                                     | Product info             | Product information   |                                | General Product<br>Information  |         | Electrical Data  |              |                           |
|-------------------------------------|--------------------------|---|--------------------------------|---------------------------------|---------|--|--------------|---------------------------|
| Product description                 |                          | Application (Category<br>and Product specific)                  |                                | Global order<br>reference       |         | Nominal voltage  |              | Nominal wattage           |
| Lightbar VX1000-CB SM <sup>1)</sup> | Additional I application | l high beam LEDDL120-CB SR<br>n                                 |                                |                                 | 12/24 V |  | 108 W        |                           |
|                                     |                          | Photomet  | ic Data LED modu<br>informatio |                                 |         | Lifetime<br>Data   | Capabilities |                           |
| Product description                 | Test<br>voltage          | Nominal li<br>flux  | uminous                        | Number of<br>LEDs per<br>module |         | Lifespan Technology<br>Tc  |              | ology                     |
| Lightbar VX1000-CB SM <sup>1)</sup> | 13.2 V                   | 13.2 V 6000 lm 36   Certificates &<br>standards Logistical data |                                |                                 | 5000 hr | LED  | 2)           |                           |
|                                     |                          |   |                                | Logistical data                 |         | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACh) |              |                           |
| Product description                 | ECE referen<br>number    | ECE reference<br>number   |                                | Commodity code                  |         | Candidate list<br>substance 1  |              | CAS No. of substance<br>1 |
| Lightbar VX1000-CB SM <sup>1)</sup> | 37.5 + 37.5              | 37.5 + 37.5   |                                | 85122000900                     |         | Lead   |              | 7439-92-1                 |

| Product description                 | Safe use instruction  | Declaration no. in<br>SCIP database      |
|-------------------------------------|---|--|
| Lightbar VX1000-CB SM <sup>1)</sup> | The identification of<br>the Candidate List<br>substance is<br>sufficient to allow<br>safe use of the<br>article. | d05be9e0-c08f-48c6-<br>a54d-36640953ffa9 |

<sup>1)</sup> Beam Pattern: Combo

<sup>2)</sup> Light-emitting diode application

# Product family datasheet

#### Download Data

|   | File   |
|---|--|
| Z | User instruction<br>GPRS_Safety symbols instructions         |
| Z | Brochures<br>OSRAM Lightbar VX1000-CB SM Flyer (DE)          |
| 7 | Brochures<br>OSRAM Lightbar VX1000-CB SM Flyer (EN)          |
| D | Video<br>Video OSRAM LEDriving driving & working             |
| D | Video<br>Product Video OSRAM LEDriving Lightbar VX1000-CB SM |

#### Legal advice

Legal advice:The installation of the OSRAM LEDriving Lightbar VX1000-CB SM is fully ECE compliant and therefore registrationfree. This does not include individual custom requirements of countries, in addition to the standardized ECE certification of the product. 1) Precise terms and conditions at: www.osram.com/am-guarantee2)OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.Refer to www.osram.com/am-guarantee for precise conditions

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.