## **OSRAM**

# LEDinspect WEARABLE NECKLIGHT





#### **Detachable Torches**

High flexibility - can be placed around the neck, on the head, in the hand or on a magnetic surface



## Up to 265 lm (high) & 130 lm (low)

Two light functions: Up to 265 lm ( high) and up to 130 lm ( low)



### Approx. 1.5 hours charging time

With a charging time of only approx. 1.5 hours, this OSRAM light is quickly ready for use again



#### 2-year OSRAM Guarantee\*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

#### Product family datasheet



#### Light is versatile

This rechargeable neck light with two individually detachable torches from OSRAM is perfect for professional and private use. With two light functions up to 265lm (high), 130lm (low) and an adjustable 90 degree angle, this offers different setting options for a variety of tasks. The LEDinspect Wearable Neck Light is particularly impressive with its great flexibility - it can be used around the neck, on the head, in the hand or on a magnetic surface. The rechargeable battery allows up to 3 hours of operation at high power or up to 4.5 hours at low power and with a charging time of only about 1.5 hours, this OSRAM lamp is also quickly ready for use again. A USB Micro B charging cable with two connections for the individual lamps to charge the lithium battery is included. In accordance with protection class IP54, this lamp has protection against the ingress of dust particles and against splashing water and has been tested for impact resistance in accordance with IK07. With a weight of only 115g and the flexible design, the product is easy to store and transport and is therefore ideal as a light for handicraft work, craft activities, car repairs and in everyday life. OSRAM also provides a 2-year guarantee\* \*For precise conditions please refer to: www.osram.com/amguarantee

### Product family datasheet

#### Technical data

	Product inform	Product information		General Product Information		Electrical Data		
Product description		Application (Category and Product specific)		Global order reference		age	Nominal voltage	
INSPECTION LAMP	LED inspection	LED inspection lights		LEDIL413			3.7 V	
	Photometric Da	ata				Physica Dimens	l Attributes & ions	
Product description	Color temperat	Color temperature		Nominal luminous flux		Product weight		
INSPECTION LAMP	6500 K	6500 K			White	115.00 g		
							LED module information	
Product description	Length	Length		Width			Number of LEDs per module	
INSPECTION LAMP	158.0 mm		25.0 mm		150 mm		1+1	
	Colors & mater	Colors & materials		Additional product data				
Product description	Base color	Base color		Type of Battery		Number of included batteries		
INSPECTION LAMP	Black / Orange		2 years	Recharge	eable	1		
	Capabilities	Certific standa	cates & rds	Logistical data		Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Product description	Technology	IK Clas	s	Watt ho	our per battery	Candida substar		
INSPECTION LAMP	LED	IK07		2.96		Lead		

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
INSPECTION LAMP	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9b7cd37b-d0e8- 4a84-abf2- d10e9bfc7dfe

### Product family datasheet

#### Legal advice

Application advice: For more detailed application information and graphics please see product datasheet and the user instruction.\* for precise conditions please refer to:

www.osram.com/am-guarantee

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### **Disclaimer**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.