

# LEDriving HL VINTAGE H7/H18

LEDriving high and low beam lamps





# Warm White color temperature of 2,700 K

The precise halogen-like color temperature creates a perfect stylish old-fashioned look for your car



#### Up to +260% more brightness

Better visibility thanks to high lumen output: more light allows to see farther and therefore react sooner. Compared to minimum ECE R112 for H7/H18.



4-year OSRAM guarantee

For precise conditions, please refer to www.osram.com/am-guarantee



# High-performing LED retrofit lamp providing improved visibility even for old-designed and aged headlights

With up to +300% more brightness1), the OSRAM LEDriving HL Vintage retrofit lamp ensures optimum visibility and thus allowing drivers to recognize, obstacles and hazards sooner than conventional lamps. This LED retrofit lamp not only creates a stylish old fashioned look with a warm white color temperature of 2,700K but also offers reduced glaring thanks to an optimized light distribution thus avoids blinding other drivers on the racetrack. The lamps result in very stable electric behaviour even when installed on old electric circuits. Premium OSRAM quality and LED technology grant up to 5 times more lifetime (compared to traditional halogen bulbs). The pair of lamps comes with a 4-year OSRAM guarantee2).

The LEDriving HL Vintage high and low beam lamps by OSRAM replace conventional halogen lamps and are 12V compatible. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. Drivers can enjoy the advantages of the LED technology without high temperature, without UV emission, lower current absorption and longer lifetime in the headlights and with no impact on the old timer's aesthetics.

 compared to ECE R112, for R2/H4/H19
 For precise guarantee conditions please refer to www.osram.com/amguarantee

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

#### Technical data

	Product information			General Product Information	Electrical	Electrical Data	
Product description	Product type (off- road vs. on-road)	••	on (Category uct specific)	Global order reference	Power input	Nominal voltage	
LEDriving HL VINTAGE ≙ H7/H18	Off-road ≜ H7/H18	<ul> <li>Mainly us</li> <li>Beam, Hig</li> <li>and Fog li</li> <li>applicatio</li> </ul>	ight	64210DWVNT Photometric Data	18 W	12.0 V Physical Attributes &	
Product description	Nominal w	vattage	Test voltage	Nominal luminous flux	Luminous flux tolerance	Dimensions Diameter	
LEDriving HL VINTAGE ≜ H7/H18	19 W		13.2 V	1600 lm	±20 %	14.0 mm	
	1 :	<b></b>	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)				
	Lifetime Data	Capabilities	Informati	• •		(EC) 1907/2006	
Product description		Technology	Informati	on according Art. 33 rticle Candi		(EC) 1907/2006 CAS No. of substance 1	

Product description	Safe use instruction	Declaration no. in SCIP database
LEDriving HL VINTAGE ≜ H7/H18	The identification of the Candidate List substance is sufficient to allow safe use of the article.	c9d11607-516c- 47d2-82bf- 1bbe99acc048

#### Download Data

	File
*	User instruction GPRS_Safety symbols instructions
★	User instruction LEDriving HL VINTAGE

#### **Application advice**

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.