OSRAM

NIGHT BREAKER H7-LED GEN2

OSRAM's first NIGHT BREAKER H7 LED for motorcycles





The NIGHT BREAKER LED family - OSRAM's first street-legal 1) LED retrofit lamps.



Up to 230% more brightness 2) & 6000K

See and be seen with OSRAM. Cool white color temperature similar to daylight. For more safety on the road, especially when driving at night



Vibration resistance

Specially developed vibration-resistant and energy-efficient design for an up to 5 times longer lifetime 3)



4 Year OSRAM Guarantee⁴⁾

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.



With the NIGHT BREAKER LED GEN 2, OSRAM's first street $\log a^{(1)}$ H7 LED retrofit lamp for motorcycles is now on the market.

With the street-legal1) NIGHT BREAKER LED GEN 2 H7 you can now upgrade the function of your high- and low beam lights of your motorcycle to state-of-the-art LED technology. These LED replacement lamps are suitable as a replacement for conventional H7 lamps and bases. They offer a modern and bright white light with a color temperature of up to 6000 Kelvin and impress with up to 230% more brightness2), while the glare of other road users falls below the permissible maximum values by up to 50%2). In comparison to standard lamps, such as halogen lamps, these LED retrofit lamps consume up to 60% less energy and convince thanks to the LED technology and the specially developed vibration-resistant design, with up to 5 times longer life time3). You can now replace your motorcycle lamps with OSRAM's revolutionary NIGHT BREAKER LED retrofit lamps and experience trend-setting brightness with road approval1) Additionally, OSRAM offers a dedicated guarantee on all NIGHT BREAKER LED retrofit lamps2)

Technical data

	Product in	formation							
Product description	Product le	Product legal advice		Product legal advice 2		Product legal advice 3		Application (Category and Product specific)	
NIGHT BREAKER GEN2 H7 LED	1) Approved LED light source - only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led		2) Compared to minimum ECE R112. On top with 50% less glare.		3) Compared to halogen lamps		High and low beam		
	General Product Information		Electrical	Data					
Product description	Global order reference		Power input	Test voltage	Power input toleranc e	input voltage toleranc			
NIGHT BREAKER GEN2 H7 LED	64210DW	64210DWNBG2		13.2 V	±10 %	16 W	1	2.0 V	
	Photomet	ric Data						Physica Attribut es & Dimens ons	
Product description	Color tem	Color temperature		Nominal luminous flux		Luminous flux tolerance		Product weight	
NIGHT BREAKER GEN2 H7 LED	6000 K		1500 lm		±10 %		Cool white	60.00 g	
							Lifetime Data	a	
Product description	Length	Length		Lamp base		Diameter		Lifespan Tc	
NIGHT BREAKER GEN2 H7 LED	77.9 mm	77.9 mm		PX26d		13.9 mm		2500 hr	
		Capabilities	s Certificates & standards		Inform	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		J	
Product description	Lifespan B3	Technology	Standa	rds	Primary article identifier		Candidate list substance 1		
NIGHT BREAKER GEN2 H7 LED	1500 hr	LED	ABG		40621	72383301	Lead		

Product description	CAS No. of substance	Safe use instruction	Declaration no. in SCIP database
NIGHT BREAKER GEN2 H7 LED	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	57741e82-9d0a- 42dc-9cd2- 762ae29b617a

Download Data

File



User instruction
GPRS_Safety symbols instructions

Safety advice

Application advice: For more detailed application information and graphics please see product datasheet and user manual.

Legal advice

- 1) Approved LED light source only applies to the respective countries in which there is approval or to which an equivalent approval applies and the vehicle models and light functions currently listed in the compatibility list. For more details see www.osram.com/nb-led
- 2) Compared to the minimum requirements of ECE R112, while the glare is below the maximum permissible values by up to 50%
- 3) In comparison to traditional Halogen lamps
- 4) For precise conditions please refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

