Product family datasheet

OSRAM

LEDinspect DUAL CHARGE PAD



Wire-Free Technology Simply place a compatible worklight on the charging pad to easily hold and recharge



Flexible mounting options With strong magnets and screw holes built-in, you can easily attach the charging pad to toolboxes, workbenches and more



Built to last IK08 and IP20 rated to survive the rigors of the professional workshop



The easiest way to recharge two inspection lamps

Removing the need to find and connect the correct charging cable, OSRAM's Wire-Free charging pad securely stores and recharges a pair of suitable inspection lamps, so they are ready when you are. This innovative design not only enhances convenience but also supports an uninterrupted workflow.

Product family datasheet

Technical data

	Product information	General Product Information	Physical Attributes & Dimensions Product weight Length		Dimensions
Product description	Application (Category and Product specific)	Global order reference			Length
CHARGING PAD	LED inspection lights	LEDIL424	220.00 g		202.2 mm
			Lifetime Data	Capabili	ties
Product description	Width	Height	Guarantee	Technol	ogy
i i ouuce uesenption	· · · · · · · · · · · · · · · · · · ·	neight		- recimot	
CHARGING PAD	106.0 mm	105 mm	2 years	LED	
•	106.0 mm Environmental & Regu	105 mm	2 years	LED	
•	106.0 mm Environmental & Regu	105 mm	2 years	LED 6 (REACh)	

Product family datasheet

Download Data

	File
1	User instruction LEDinspect SINGLE CHARGE PAD DUAL CHARGE PAD

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.